Exploring the Market Applications of PSA-Backed Gaskets and Laminated Solutions

By Rebecca Blose, Magnum Tapes & Films

Pressure-sensitive adhesive (PSA) tapes laminated to engineered substrates have become a go-to solution for both bonding and gasketing across a wide range of industries. Unlike structural adhesives that require cure time, PSA systems bond with simple pressure—sometimes with a bit of heat—through viscoelastic wet-out and surface interaction. That immediate bond is a big part of the appeal on the manufacturing floor.

'

What really expands their usefulness, though, is the ability to laminate PSA to a variety of materials—EPDM, XLPE, polyurethane foams, cork, felt, flock, and nonwoven batting, among others. Once combined, these materials are no longer just tape—they become functional components that can seal, cushion, isolate vibration, manage airflow, or protect surfaces.

This article focuses less on what PSA tapes are and more on where they are actually used, and how substrate + adhesive combinations are selected based on performance requirements like sealing, MVTR (moisture vapor transmission rate), temperature resistance, and long-term durability.

PSA + Substrate: Functional Systems Design

A PSA tape is best understood as a layered construction rather than a single material. In most cases, it includes:

- An adhesive (acrylic, rubber, silicone, or hybrid)
- Sometimes a carrier (film, tissue, scrim, foam, or transfer construction)
- A functional substrate (foam, rubber, fiber, or other specialty gasketing material)

The substrate drives the physical behavior—compression, recovery, sealing—while the PSA determines how well the system bonds to the target surface.

Common Substrates and Where They Fit

EPDM: A closed-cell rubber with strong UV and weather resistance. This is a staple for outdoor gasketing, especially where long-term exposure is expected.

XLPE Foam: A crosslinked polyethylene with a uniform cell structure and low compression set. Often used where consistent thickness, gap fill and clean sealing surfaces matter.

Polyurethane (PU) Foams: Available in both open and closed cell forms. These are highly tunable materials—used where airflow, MVTR, or compressibility need to be controlled.

Cork and Cork-Rubber: Naturally compressible with good recovery. Particularly useful in vibration damping or where mating surfaces are uneven.

Felt and Flock: Soft, fibrous materials used more for noise reduction, anti-rattle, or surface protection than sealing.

Batting / Nonwovens: Lightweight and breathable. These show up in filtration, acoustics, and medical applications.

General Industrial: Everyday Use

In general industrial settings, PSA-laminated materials are often used in ways that don't get much attention—but they are everywhere!

Enclosure sealing is a good example. Electrical cabinets, HVAC housings, and control panels all rely on foam-based PSA gaskets to keep out dust and moisture. These are typically applied around doors, access panels, and seams.

Vibration isolation is another common use. Cork, felt, or PU foam with PSA backing can be applied between panels or components to reduce noise and mechanical wear—especially in compressors or sheet metal assemblies.

Mounting and bonding applications also benefit from PSA systems. Double-coated tapes eliminate the need for drilling or fasteners when attaching nameplates, trim pieces, or lightweight panels.

And then there are surface protection applications—felt or flock tapes placed at contact points to prevent scratching or reduce friction in sliding assemblies.

Transportation Applications

PSA-laminated tapes are deeply integrated into transportation manufacturing, often replacing mechanical fastening or liquid sealants.

Automotive: Some of the most common applications include:

- Door seals and weatherstripping (typically EPDM with acrylic PSA)
- Wire harness wrapping and anti-rattle (fleece or felt tapes)
- Interior trim attachment
- HVAC sealing and airflow management using foam gaskets

These materials work well in automotive environments because they conform to complex shapes, help manage NVH (noise, vibration, harshness), and support high-speed assembly processes.

Marine, Rail, and Bus
In these segments, environmental exposure becomes more critical. Typical applications include:

- Window and hatch sealing
- Panel bonding and vibration damping
- Flooring systems (underlayment or anti-slip interfaces)

Here, materials like EPDM and XLPE are commonly used due to their resistance to moisture, temperature swings, and—in marine settings—saltwater exposure.

Building and Construction
One of the fastest-growing areas for PSA-laminated materials is in the building envelope, where air sealing and moisture control are critical.

Windows and Doors: PSA-backed gaskets are widely used in:

- Window frame perimeter seals
- Insulating glass (IG) unit gasketing
- Spacer and glazing systems

A good example is the use of low MVTR polyurethane foam combined with an acrylic PSA in IG units. In this case, controlling moisture ingress is essential to prevent fogging inside the glass assembly. The gasket needs to seal effectively while maintaining the right vapor transmission characteristics.

Wall Systems and Siding
PSA tapes are often hidden but essential in wall assemblies:

- Behind siding as sealing strips
- Along sheathing joints to maintain air barrier continuity
- Around penetrations like pipes and vents

XLPE foams are often selected for their consistency and compression performance, while EPDM is used where UV exposure or weathering is a concern.

Roofing and HVAC
In HVAC systems, foam tapes are used to seal ductwork and prevent air leakage. PSA-backed gasketing ensures tight joints in air handling systems, improving efficiency.

They also show up in roofing systems—particularly in flashing details and membrane overlaps where quick, reliable sealing is needed.

Interior Finishing
Inside the building, these materials are used more for comfort and finish quality:

- Felt or flock tapes under flooring to reduce noise
- Cork tapes in expansion joints
- Foam tapes behind trim, drywall, or ceiling systems
- Foams and films for interior mounting and panel installation

Medical Applications
Medical uses of PSA-laminated materials are more specialized but follow the same basic principles.

Wearable devices rely on foam or nonwoven PSA tapes that adhere to skin while remaining removable without irritation.

Wound care products often use PU films or foams with medical-grade adhesives to create breathable, protective barriers.

Filtration and venting applications use nonwoven materials laminated with PSA to manage airflow while blocking contaminants in device housings.

Electronics and Specialty Uses
In electronics, PSA systems are often doing very precise jobs:

- EMI/RFI shielding using conductive foams or fabrics
- Thermal interface bonding
- Light blocking and gasketing in displays

These applications require tight tolerances—PSA helps eliminate gaps and maintain consistent contact without adding mechanical complexity.

Matching Substrate to Application
Substrate selection ultimately comes down to the function required:

- EPDM for weather sealing and outdoor durability
- PU foam where MVTR or compressibility needs to be controlled
- XLPE for consistent gasketing and low compression set
- Cork for vibration damping
- Felt/fleece for noise reduction
- Nonwovens for breathable or filtration applications

PSA Chemistry Still Matters
While the substrate gets most of the attention, the adhesive itself is just as important.

- Acrylic PSAs are the default for many applications due to UV stability and long-term performance
- Rubber-based PSAs offer high initial tack and are often used in general-purpose or temporary applications
- Silicone PSAs are reserved for high-temperature environments or difficult-to-bond surfaces

Transfer adhesives and double-coated constructions are often used depending on how much conformability or dimensional stability is needed.

Converting and Design Considerations
Most PSA-laminated materials are supplied as:

- Die-cut gaskets
- Rolls or sheets
- Parts designed for automated assembly

A few practical considerations always come into play:

- Surface energy of the bonding substrates
- Compression set and long-term recovery
- Temperature exposure
- Environmental conditions (UV, moisture, chemicals)

And as simple as PSA systems are, performance still depends heavily on proper application—clean surfaces, adequate pressure, and appropriate temperature.

Closing Thoughts

PSA-laminated tapes have evolved well beyond simple fastening solutions. In many cases, they are designed into products as functional components—handling sealing, damping, insulation, and bonding all at once. PSA backed component designs are being adopted at a more rapid rate across many markets and applications than ever before.

You'll find them in automotive door systems, behind siding and window frames, inside medical devices, and throughout industrial equipment. The common thread is efficiency: faster assembly, fewer parts, and consistent performance.

At the end of the day, success with these materials comes down to pairing the right adhesive with the right substrate for the environment it will live in. Whether that means EPDM for outdoor exposure, PU foam for controlled permeability, or cork for vibration isolation, the goal is always the same—match the material to the real-world demands of the application.

NEW GFA MEMBERS

REGULAR MEMBERS

Reilly Foam Corp
West Palm Beach, FL
reillyfoam.com

ASSOCIATE MEMBERS

Allfi Waterjet Inc.
Miamiville, OH
allfiwaterjet.com

PPD Rubtech
Waterville, QC
ppdgroup.com

RM Biltrite LLC
Sandy Springs, GA
rmbiltrite.com

Starflex America Inc.
Houston, TX
starflexamerica.com

TECHTEAM™

How Does TechTeam™ Work?

1 Have a question come up while working on a project?





2 Submit your inquiry through our portal.

3 Our experts will review and discuss your submission.





4 The experts will reach out with solutions or further ideas.

5 Apply the solutions with the knowledge at your hands.



GFA Members can access TechTeam from the Member Dashboard after logging in to the GFA's website (www.gasketfab.com). TechTeam will quickly and confidentially provide unbiased, expert support to save you time, money, and materials.

TechTeam™ is provided in partnership with the International Association of Diecutting and Diemaking.